

Finex™

Air Spray Guns



HVL Pressure Feed

Mini Gravity Feed

HVL Gravity Feed

Lightweight, Ergonomic Air Spray Guns:

- Aircaps optimized for high quality spray performance
- Lightest trigger pull in its category
- Integrated air inlet adjustment (cheater) valve
- Durable stainless steel trigger comes standard on all Finex gun models

Finex Pressure Feed Guns:

- Available in HVL and Conventional technologies
- Needle/nozzle sizes offered in 0.04" (1.0 mm), 0.05" (1.2 mm), 0.055" (1.4 mm) and 0.07" (1.8 mm)

Finex Gravity Feed Guns:

- Mini and Standard Gravity Feed offered in a wide variety of needle/nozzle sizes
- Plastic cup included with the gun
- 3M™ PPS™ and aluminum cups available

Ordering Information for Finex Guns and Accessories

Gun Style	Gun Part Number	Needle/Nozzle Size		Needle, Nozzle Air Cap Kit	Needle Packing Kit	Gravity Cup Kits	PPS Adapter	Trigger Repair Kit (stainless steel)
		in	mm					
Pressure Feed Standard HVLP	289247	0.039	1.0	289301	288891			24F061
	289248	0.047	1.2	289302				
	289249	0.055	1.4	289303				
	289250	0.071	1.8	289304				
Pressure Feed Conventional	289252	0.039	1.0	289306	288891			24F061
	289253	0.047	1.2	289307				
	289254	0.055	1.4	289308				
	289255	0.071	1.8	289309				
Gravity Feed Mini-HVLP	289256	0.024	0.6	289286	288890	289323 (125 cc Plastic)	289520	24F059
	289257	0.031	0.8	289287				
	289258	0.039	1.0	289288				
	289259	0.047	1.2	289289				
	289260	0.055	1.4	289290				
Gravity Feed Standard Conventional	289243	0.051	1.3	289292	288891	289322 (600 cc Plastic)	289520	24F061
	289244	0.055	1.4	289293				
	289245	0.059	1.5	289294				
	289246	0.071	1.8	289295				
Gravity Feed Standard HVLP	289238	0.051	1.3	289297	288891	289322 (600 cc Plastic)	289520	24F061
	289239	0.055	1.4	289298				
	289240	0.059	1.5	289299				
	289241	0.071	1.8	289300				

Technical Data

Maximum air inlet pressure	100 psi (7 bar, 0.7 MPa)
Maximum fluid working pressure	100 psi (7 bar, 0.7 MPa)
Gravity Feed:	
Maximum HVLP inbound air pressure.	29 psi (2 bar, 0.2 MPa)*
Pressure Feed:	
Maximum HVLP inbound air pressure.	24 psi (1.7 bar, 0.17 MPa)*
Air consumption	
Mini HVLP Gravity	7.0 SCFM at 29 psi (2.0 bar, 0.2 MPa)
Conventional Gravity	9.5 SCFM at 43 psi (3.0 bar, 0.3 MPa)
HVLP Gravity	9.5 SCFM at 29 psi (2.0 bar, 0.2 MPa)
HVLP Pressure	11.8 SCFM at 24 psi (1.7 bar, 0.17 MPa)
Conventional Pressure	11.0 SCFM at 50 psi (3.4 bar, 0.34 MPa)
Fluid and air operating temperature range	32-109°F (0-43° C)
Spray Gun	
Air inlet.	1/4 npsm (R1/4-19)
Fluid inlet (pressure feed)	3/8-18 npsm (R3/8-19)
Mini HVLP Gravity weight with cup	0.9 lb (0.4 kg)
Gravity Feed weight with cup	1.1 lb (0.5 kg)
Pressure Feed weight	0.8 lb (0.37 kg)
Wetted parts.	Aluminum, stainless steel, engineered plastic

*Produces 10 psi (0.07 MPa, 0.7 bar) spraying pressure at aircap.

Accessories

3M's PPS Accessories	
For use with gravity feed guns	
6 oz (150 ml) 3M PPS	
234941	Cup and Collar (box of 8)
234940	Lid and Liner (box of 50)
234942	Measurement Insert (box of 50)
25 oz (650 ml) 3M PPS	
234771	Cup and Collar (box of 8)
234772	Lid and Liner (box of 50)
15F531	Measurement Insert (box of 100)
32 oz (850 ml) 3M PPS	
234937	Cup and Collar (box of 4)
234938	Lid and Liner (box of 25)
234939	Measurement Insert (box of 100)
Aluminum Cups	
289858	125 cc Aluminum
289860	600 cc Aluminum



For more information visit www.graco.com/finishing or call 1-877-844-7226

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.
877.84GRACO (1-877-844-7226) or visit us at www.graco.com.

©2014 Graco Inc. Form No. 339461 Rev. C 2/14 Printed in the U.S.A.
 All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

