

GPM	Fan Width - Inches										LPM
	2 - 4	4 - 6	6 - 8	8 - 10	10 - 12	12 - 14	14 - 16	16 - 18	18 - 20		
0.05	107	207	307	407							0.20
0.09	109	209	309	409	509	609					0.33
0.12	111	211	311	411	511	611					0.49
0.18	113	213	313	413	513	613	713	813			0.69
0.24	115	215	315	415	515	615	715	815			0.91
0.31	117	217	317	417	517	617	717	817	917		1.17
0.38		219	319	419	519	619	719	819	919		1.47
0.47		221	321	421	521	621	721	821	921		1.79
0.57		223	323	423	523	623	723	823	923		2.15
0.67		225	325	425	525	625	725	825	925		2.54
0.74			327	427	527	627	727	827	927		2.96
0.90			329	429	529	629	729	829	929		3.42
1.03			331	431	531	631	731	831	931		3.90
1.17			333	433	533	633	733	833	933		4.42
1.31			335	435	535	635	735	835	935		4.98
1.47			337	437	537	637	737	837	937		5.56
1.63			339	439	539	639	739	839	939		6.18
1.80			341	441	541	641	741	841	941		6.83
1.98			343	443	543	643	743	843	943		7.51
2.17				445	545	645	745				8.23
2.37				447	547	647	747				8.98
2.58				449	549	649	749				9.76
2.79				451	551	651	751				10.57
3.00				453	553	653	753				11.35
3.25				455	555	655	755				12.29
4.26				463	563	663	763				16.13
4.43				465	565	665	765				17.17
	5 - 10	10 - 15	15 - 20	20 - 25.5	25.5 - 30.5	30.5 - 35.5	35.5 - 40.5	40.5 - 46	46 - 51		

Fan Width - Centimeters

### FT2207 TIPS

FT2207 tips have a 7500 PSI (500 BAR) MWP for maximum pressure spray applications. This simple 3-component design makes tip changes on the job quick and safe.

**7500 PSI (500 BAR)**

**Part No.: FT2207-XXX**



GPM	Fan Width - Inches										LPM
	2 - 4	4 - 6	6 - 8	8 - 10	10 - 12	12 - 14	14 - 16	16 - 18	18 - 20		
0.05	107	207	307	407							0.20
0.09	109	209	309	409	509	609					0.33
0.12	111	211	311	411	511	611					0.49
0.18	113	213	313	413	513	613	713	813			0.69
0.24	115	215	315	415	515	615	715	815			0.91
0.31	117	217	317	417	517	617	717	817	917		1.17
0.38		219	319	419	519	619	719	819	919		1.47
0.47		221	321	421	521	621	721	821	921		1.79
0.57		223	323	423	523	623	723	823	923		2.15
0.67		225	325	425	525	625	725	825	925		2.54
0.74			327	427	527	627	727	827	927		2.96
0.90			329	429	529	629	729	829	929		3.42
1.03			331	431	531	631	731	831	931		3.90
1.17			333	433	533	633	733	833	933		4.42
1.31			335	435	535	635	735	835	935		4.98
1.47			337	437	537	637	737	837	937		5.56
1.63			339	439	539	639	739	839	939		6.18
	5 - 10	10 - 15	15 - 20	20 - 25.5	25.5 - 30.5	30.5 - 35.5	35.5 - 40.5	40.5 - 46	46 - 51		

Fan Width - Centimeters

### FT2200 TIPS

FT2200 tips are available in 122 sizes of fan width and orifice combinations so you can match the right tip to every coating you spray.

**5000 PSI (345 BAR)**

**Part No.: FT2200-XXX**



**Safety Guard** fits most major manufacturers' airless spray guns and accepts most tips. Large knurls for a sure grip.

**5000 PSI (345 BAR)**

**Part No.: FT2200-999 - 7/8" Thread Size**  
**Part No.: FT2200-998 - 11/16" Thread Size**



**Safety Guard** fits most major manufacturers' airless spray guns and accepts most tips. All metal parts are stainless steel for durability.

**7500 PSI (500 BAR)**

**Part No.: FT2207-999 - 7/8" Thread Size**  
**Part No.: FT2207-998 - 11/16" Thread Size**



**Part No.: FT1101-201 - Metal Saddle Seal**

**Part No.: FT1101-403 - Gasket**

**Part No.: FT2200-901 - Seal & Gasket**

**Part No.: FT2200-995 - Seal & Gasket 5 Pack**

GPM	Fan Width - Inches								LPM	
	2 - 4	4 - 6	6 - 8	8 - 10	10 - 12	12 - 14	14 - 16	16 - 18		18 - 20
0.05	107	207	307	407						0.20
0.09	109	209	309	409	509	609				0.33
0.12	111	211	311	411	511	611				0.49
0.18	113	213	313	413	513	613	713	813		0.69
0.24	115	215	315	415	515	615	715	815		0.91
0.31	117	217	317	417	517	617	717	817	917	1.17
0.38		219	319	419	519	619	719	819	919	1.47
0.47		221	321	421	521	621	721	821	921	1.79
0.57		223	323	423	523	623	723	823	923	2.15
0.67		225	325	425	525	625	725	825	925	2.54
0.74			327	427	527	627	727	827	927	2.96
0.90			329	429	529	629	729	829	929	3.42
1.03			331	431	531	631	731	831	931	3.90
1.17			333	433	533	633	733	833	933	4.42
1.31			335	435	535	635	735	835	935	4.98
1.47			337	437	537	637	737	837	937	5.56
1.63			339	439	539	639	739	839	939	6.18
1.80			341	441	541	641	741	841	941	6.83
1.98			343	443	543	643	743	843	943	7.51
2.17				445	545	645	745			8.23
2.37				447	547	647	747			8.98
2.58				449	549	649	749			9.76
2.79				451	551	651	751			10.57
3.00				453	553	653	753			11.35
3.25				455	555	655	755			12.29
4.26				463	563	663	763			16.13
4.43				465	565	665	765			17.17
	5 - 10	10 - 15	15 - 20	20 - 25.5	25.5 - 30.5	30.5 - 35.5	35.5 - 40.5	40.5 - 46	46 - 51	

Fan Width - Centimeters

### FT2208 TIPS

Uses carbide pressed into a high grade stainless steel housing. A stainless steel insert is pressed behind the carbide to increase laminar flow and improve atomization. The insert also improves the life of the carbide because less pressure is required to achieve atomization.

5000 PSI (345 BAR)

Part No.: FT2208-XXX



### FLAT TIP SAFETY GUARD

Fits all major manufacturers' airless spray guns. Flat tips "lock" into cavity for positive alignment.

5000 PSI (345 BAR)

Part No.: FT2205-999 - 7/8" Thread Size

Part No.: FT2205-998 - 11/16" Thread Size



GPM	Fan Width - Inches								LPM	
	2 - 4	4 - 6	6 - 8	8 - 10	10 - 12	12 - 14	14 - 16	16 - 18		18 - 20
0.05	107	207	307	407						0.20
0.09	109	209	309	409	509	609				0.33
0.12	111	211	311	411	511	611				0.49
0.18	113	213	313	413	513	613	713	813		0.69
0.24	115	215	315	415	515	615	715	815		0.91
0.31	117	217	317	417	517	617	717	817	917	1.17
0.38		219	319	419	519	619	719	819	919	1.47
0.47		221	321	421	521	621	721	821	921	1.79
0.57		223	323	423	523	623	723	823	923	2.15
0.67		225	325	425	525	625	725	825	925	2.54
0.74			327	427	527	627	727	827	927	2.96
0.90			329	429	529	629	729	829	929	3.42
1.03			331	431	531	631	731	831	931	3.90
1.17			333	433	533	633	733	833	933	4.42
1.31			335	435	535	635	735	835	935	4.98
1.47			337	437	537	637	737	837	937	5.56
1.63			339	439	539	639	739	839	939	6.18
	5 - 10	10 - 15	15 - 20	20 - 25.5	25.5 - 30.5	30.5 - 35.5	35.5 - 40.5	40.5 - 46	46 - 51	

Fan Width - Centimeters

### FT2205 TIPS

A full range of sizes with large fluid capacity.

5000 PSI (345 BAR)

Part No.: FT2205-XXX





### Tip Extensions - Aluminum

Tip extensions give you extra reach for spraying soffits, high ceilings and reduce back fatigue when spraying floors and decks. Moving the spray head away from you also keeps you and your equipment cleaner. Includes 2200 Tip Guard.

### Tip Extensions, Aluminum - 4200 PSI (290 BAR) MWP

Part No.	Description
FT1110-212	10" w/ 2200 Guard - 7/8" threads
FT1110-232	10" w/ 2200 Guard - 11/16" threads
FT1110-213	15" w/ 2200 Guard - 7/8" threads
FT1110-233	15" w/ 2200 Guard - 11/16" threads
FT1110-214	20" w/ 2200 Guard - 7/8" threads
FT1110-234	20" w/ 2200 Guard - 11/16" threads
FT1110-215	30" w/ 2200 Guard - 7/8" threads
FT1110-235	30" w/ 2200 Guard - 11/16" threads

### Tip Extensions - Stainless Steel

Manufactured from the highest quality stainless steel for high pressure applications.

### Airless Tip Extensions, Stainless Steel - 7,500 PSI MWP

Part No.	Description
FT1110-225	36" Stainless Steel extension
FT1110-227	60" Stainless Steel extension



### Pole Extensions- Aluminum

Made from strong and lightweight aluminum alloy extrusions for spray or pressure roll applications. Smooth ribbed 1" (2.5cm) diameter for a sure, comfortable grip. Poles can be combined to create different lengths to suit your application. (Maximum length should not exceed 10.5' (3.2m))

### Pole Extensions - Aluminum - 4200 PSI (290 BAR) MWP

Part No.	Description
FT1106-020	18" - 7/8" threads
FT1106-021	18" - 11/16" threads
FT1106-022	36" - 7/8" threads
FT1106-023	36" - 11/16" threads
FT1106-024	72" - 7/8" threads
FT1106-025	72" - 11/16" threads



### Adjustable Angle Spray Head

Attach to your tip extension pole extension or direct to your spray gun to spray at a variety of angles. 260 degrees of rotation allows you to quickly and safely adapt to nearly any spray application.

### Airless Swivel Head - 4200 PSI (290 BAR) MWP

Part No.	Description
FT1101-515	Swivel Head - 7/8" Threads
FT1101-520	Swivel Head - 11/16" Threads



### 90° Angle Adapter

Attach between your spray gun and extension pole to improve comfort. Ideally suited for overhead spraying such as ceilings and trusses.

### Airless 90° Adapter - 4200 PSI (290 BAR) MWP

Part No.	Description
FT1106-041	90° Adapter - 7/8" Threads
FT1106-042	90° Adapter - 11/16" Threads