



Electric Sprayers

Latin America

Graco's Complete Line of Professional Electric Airless Sprayers



PROVEN QUALITY. LEADING TECHNOLOGY.

390/ 390S

If you need a solid workhorse of a sprayer that is built for the professional who is just “starting out” then the 390 is for you. This is Graco’s lightest professional sprayer ideal for residential jobs because it is lightweight and portable, and delivers a quality spray pattern. Hands down, the 390 is the best value compared to any small electric sprayer.

CONFIGURATION	AVAILABLE IN
STAND	110V and 230V
HI-BOY	110V and 230V

SPECIFICATIONS	
MAX TIP SIZE:	0.021
MAX LPM:	1.8
MAX PSI (BAR):	3300 (227)
MOTOR HP:	5/8 DC

- INCLUDES**
- FTx™ Gun
 - RAC X™ 515 SwitchTip™ and Guard
 - 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose



Stand model

Features Found Only On A Graco Small Electric Sprayer



Lightweight, Ergonomic Design

- ▶ Graco’s lightest professional sprayer—weighs only 13.6 kg
- ▶ Offset handle with rubber comfort grip positions sprayer at a comfortable carrying angle
- ▶ Extremely portable

Swivel Inlet Suction Hose

- ▶ Durable, lightweight and rustproof aluminum construction
- ▶ Easily swivels to reach paint buckets or cans
- ▶ Toolless hose removal for quick cleaning or accessing inlet ball
- ▶ Attached big cup holds the inlet during transport to catch drips



Endurance Pump

- ▶ The most rugged and reliable pump on the market today—lasts 2 times longer than the next leading brand
- ▶ Long-life V-Max Blue™ packings, Chromex™ rod and hardened stainless steel cylinder
- ▶ QuickAccess™ intake valve requires only a hammer to access the intake ball to easily clean or clear debris

Easy Out Pump Filter

- ▶ Vertical design helps eliminate spills when changing the filter element
- ▶ Filters from the inside out—filters won’t get stuck or collapse when dirty
- ▶ Large 7.8 square inch filtering area reduces tip clogs



Ultra® 395

The Ultra 395’s reliability and performance has made it Graco’s most popular small electric sprayer. It features SmartControl™ 1.0 pressure control that delivers a consistent spray fan without pressure fluctuation at all spraying pressures. Proven technology and design make it perfect for professionals who spray daily with a wide range of coatings.



Hi-Boy model

CONFIGURATION	AVAILABLE IN
STAND	110V and 230V
HI-BOY	110V and 230V

SPECIFICATIONS	
MAX TIP SIZE:	0.023
MAX LPM:	2.0
MAX PSI (BAR):	3300 (227)
MOTOR HP:	7/8 TEFC DC

- INCLUDES**
- Contractor™ Gun
 - RAC X 517 SwitchTip and Guard
 - 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose



Stand model

All the features of the 390, **PLUS:**

15% higher output flow and 40% higher hp TEFC motor than the 390

SmartControl 1.0 Pressure Control

- ▶ Advanced variable speed motor control delivers a consistent spray fan without pressure fluctuation at all spraying pressures
- ▶ Lowest deadband and fast response when spraying

Contractor Gun

- ▶ Professional quality Contractor gun for longer life



Chrome Plated, Welded Steel Carts

- ▶ Retractable handle doubles as coiled hose storage
- ▶ Semi-pneumatic wheels roll easily over rough terrain
- ▶ Hi-Boy TiltBack™ kickstand cart design holds inlet clear of the paint bucket for easy one-person bucket changes
- ▶ Inlet tube fits through a 2-inch cap opening on standard 19-liter bucket



Ultra Max II 490

The Ultra Max II 490 sprayer is the ideal choice for professionals looking for superior performance and control for daily use on residential jobs.

CONFIGURATION STAND	AVAILABLE IN 110V and 230V
HI-BOY	110V and 230V
SPECIFICATIONS	
MAX TIP SIZE:	0.023
MAX LPM:	2.0
MAX PSI (BAR):	3300 (227)
MOTOR HP:	1.0 Brushless DC

- INCLUDES**
- Contractor™ Gun
 - RAC X 517 SwitchTip and Guard
 - 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose



Stand model

Ultra Max II 495

The Ultra Max II 495 brings the leading technology and performance of Graco's larger Ultra Max II models into a compact and lightweight design.

CONFIGURATION STAND	AVAILABLE IN 110V and 230V
HI-BOY	110V and 230V
LO-BOY	110V and 230V
SPECIFICATIONS	
MAX TIP SIZE:	0.025
MAX LPM:	2.3
MAX PSI (BAR):	3300 (227)
MOTOR HP:	1.2 Brushless DC

- INCLUDES**
- Contractor Gun
 - RAC X 517 SwitchTip and Guard
 - 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose



Lo-Boy model

All the features of the Ultra Max II 490, **PLUS:**
20% higher hp motor and 11% higher flow output than the Ultra Max II 490

Digital Display Available on 230 Volt Model

- ▶ Simple to use display featuring pressure display and error code
- ▶ Ideal for wide variety of coating materials used on smaller projects



Stand model



Hi-Boy model

All the features of the Ultra 395, **PLUS:**

20% lighter than the Ultra 395

Brushless motor never needs maintenance

MaxPower High Torque Brushless DC Motor

- ▶ Compact, lighter-weight motor delivers more horsepower per amp
- ▶ No brushes to change—ever!
- ▶ Enclosed design protects internal components from dirt, dust and overspray

SmartControl 2.0 Pressure Control

- ▶ Advanced technology delivers a consistent spray fan without pressure fluctuation
- ▶ Lowest dead band at lower spraying pressures makes this line of sprayers ideal for fine finish spraying

Digital Display Available on 230 Volt Model

- ▶ Simple to use display featuring pressure display and error code
- ▶ Ideal for wide variety of coating materials used on smaller projects



Hi-Boy model



Ultra Max II 695

With a 2.0 hp brushless DC motor, the Ultra Max II 695 is a rock-solid performer for the professional residential contractor who sprays a wide variety of coatings. It can handle a wide variety of tip sizes and has outstanding proven reliability.

SERIES	AVAILABLE IN
STANDARD	110V and 230V
PROCONTRACTOR	110V and 230V
LO-BOY	110V and 230V
SPECIFICATIONS	
MAX TIP SIZE:	0.031-1 Gun 0.023-2 Guns
MAX LPM:	3.6
MAX PSI (BAR):	3300 (227)
MOTOR:	2.0 hp Brushless DC

- INCLUDES**
- STANDARD SERIES AND LO-BOY UNITS:**
- Contractor Gun
 - RAC X 517 SwitchTip and Guard
 - 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose
- PROCONTRACTOR SERIES UNIT:**
- Contractor Gun
 - RAC X 517 SwitchTip and Guard
 - 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose
- AND**
- 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose

Standard Series

EVERYDAY RELIABILITY



Lo-Boy model

Hi-Boy 230 Volt model

Standard Series features found Only On A Graco:

Advantage Drive System Runs quiet and has a lifetime guarantee.

SmartControl 3.0 Pressure Control Delivers consistent spray fan without pressure fluctuations at all spraying pressures.

Endurance Pump Amazingly durable design lasts twice as long as the next leading brand.

MaxPower Brushless DC Motor Never change brushes with this maintenance-free, totally enclosed, high torque motor.

Rugged Cart Design Chrome over steel makes this durable cart last for years.

Easy Out Pump Filter Less mess when changing or cleaning the filter.

Heavy-Duty Prime Valve Maintenance-free design withstands high pressure dumping.

230 Volt Model Pressure Gauge Easy to ready gauge provides verification of pressure setting during operation.

Choose a Series that's built FOR YOU!

ProContractor Series

WORK SMARTER, FINISH MORE JOBS



All the features of the Standard Series, PLUS:

QuikReel Deploy and rewind up to 300 feet of hose in seconds without twists, kinks or coils.

Ready To Spray A total of 100 feet of hose and gun already installed.

ProConnect 2 Change out the pump using no tools in seconds resulting in quickly getting back to work.

LED Display Bright easy-to-read LED display shows pressure readout, job/lifetime/gallon counter and self diagnostics.

FastFlush Cleaning System Cleans the unit up to 4X faster using only half the water!

WatchDog Save the pump from damage when paint runs out or a hose breaks.

On-Board Toolbox End frustration and save time by never again searching for tips, filters, and tools.



Ultra Max II 695



Lo-Boy easily carries a standard 19-liters paint bucket.

Ultra Max II 795

With a 2.2 hp brushless DC motor, the Ultra Max II 795 can handle multiple guns and is ideal for the professional residential remodeling and repainting contractor who sprays a wide variety of coatings.

SERIES	AVAILABLE IN
STANDARD	110V and 230V
PROCONTRACTOR	110V and 230V
SPECIFICATIONS	
MAX TIP SIZE:	0.033-1 Gun 0.025-2 Guns 0.019-3 Guns
MAX LPM:	4.1
MAX PSI (BAR):	3300 (227)
MOTOR:	2.2 hp Brushless DC

- INCLUDES**
- STANDARD SERIES UNIT:**
- Contractor Gun
 - RAC X 517 SwitchTip and Guard
 - 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose
- PROCONTRACTOR SERIES UNIT:**
- Contractor Gun
 - RAC X 517 SwitchTip and Guard
 - 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose
- AND**
- 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose

Standard Series

EVERYDAY RELIABILITY



Standard Series features found Only On A Graco:

Advantage Drive System Runs quiet and has a lifetime guarantee.

SmartControl 3.0 Pressure Control Delivers consistent spray fan without pressure fluctuations at all spraying pressures.

Endurance Pump Amazingly durable design lasts twice as long as the next leading brand.

MaxPower Brushless DC Motor Never change brushes with this maintenance-free, totally enclosed, high torque motor.

Rugged Cart Design Chrome over steel makes this durable cart last for years.

Easy Out Pump Filter Less mess when changing or cleaning the filter.

Heavy-Duty Prime Valve Maintenance-free design withstands high pressure dumping.

230 Volt Model Pressure Gauge Easy to ready gauge provides verification of pressure setting during operation.

Choose a Series that's built FOR YOU!

ProContractor Series

WORK SMARTER, FINISH MORE JOBS



All the features of the Standard Series, PLUS:

QuikReel Deploy and rewind up to 300 feet of hose in seconds without twists, kinks or coils.

Ready To Spray A total of 100 feet of hose and gun already installed.

ProConnect 2 Change out the pump using no tools in seconds resulting in quickly getting back to work.

LED Display Bright easy-to-read LED display shows pressure readout, job/lifetime/gallon counter and self diagnostics.

FastFlush Cleaning System Cleans the unit up to 4X faster using only half the water!

WatchDog Save the pump from damage when paint runs out or a hose breaks.

On-Board Toolbox End frustration and save time by never again searching for tips, filters, and tools.



Ultra Max II 1095

With a 2.4 hp brushless DC motor and the ability to spray up to 4.5 liters per minute, the Ultra Max II 1095 is the industry standard for the large residential and commercial contractor who sprays a wide variety of coatings.

SERIES	AVAILABLE IN
STANDARD	110V and 230V
PROCONTRACTOR	110V and 230V
IRONMAN	110V and 230V

SPECIFICATIONS	
MAX TIP SIZE:	0.035-1 Gun 0.027-2 Guns 0.021-3 Guns

MAX LPM:	4.9
MAX PSI (BAR):	3300 (227)
MOTOR:	2.4 hp Brushless DC

INCLUDES

STANDARD SERIES UNIT:

- Contractor Gun
- RAC X 517 SwitchTip and Guard
- 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose

PROCONTRACTOR SERIES UNIT:

- Contractor Gun
- RAC X 517 SwitchTip and Guard
- 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose

- AND
- 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose

IRONMAN SERIES UNIT:

- Silver Plus Gun
 - RAC X 517 SwitchTip and Guard
 - 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Airless Hose
- AND
- 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax™ II Airless Hose

Standard Series

EVERYDAY RELIABILITY



Standard Series features found Only On A Graco:

Advantage Drive System Runs quiet and has a lifetime guarantee.

SmartControl 3.0 Pressure Control Delivers consistent spray fan without pressure fluctuations at all spraying pressures.

Endurance Pump Amazingly durable design lasts twice as long as the next leading brand.

MaxPower Brushless DC Motor Never change brushes with this maintenance-free, totally enclosed, high torque motor.

Rugged Cart Design Chrome over steel makes this durable cart last for years.

Easy Out Pump Filter Less mess when changing or cleaning the filter.

Heavy-Duty Prime Valve Maintenance-free design withstands high pressure dumping.

230 Volt Model Pressure Gauge Easy to ready gauge provides verification of pressure setting during operation.

Choose a Series that's built FOR YOU!

ProContractor Series

WORK SMARTER, FINISH MORE JOBS



All the features of the Standard Series, PLUS:

QuikReel Deploy and rewind up to 300 feet of hose in seconds without twists, kinks or coils.

Ready To Spray A total of 100 feet of hose and gun already installed.

ProConnect 2 Change out the pump using no tools in seconds resulting in quickly getting back to work.

LED Display Bright easy-to-read LED display shows pressure readout, job/lifetime/gallon counter and self diagnostics.

FastFlush Cleaning System Cleans the unit up to 4X faster using only half the water!

WatchDog Save the pump from damage when paint runs out or a hose breaks.

On-Board Toolbox End frustration and save time by never again searching for tips, filters, and tools.

IronMan Series

BEYOND JOBSITE TOUGH



All the features of the Standard Series, PLUS:

MaxLife Extreme Duty Pump Keeps you working by running 6X longer between repacks.

Ceramic and Stainless Steel Ball Sets Provides maximum versatility no matter what you're spraying.

ProConnect 2 Change out the pump using no tools in seconds resulting in quickly getting back to work.

Roll Cage Frame Innovative steel design withstands rugged environments and protects critical sprayer components.

LED Display Bright easy-to-read

LED display shows pressure readout, job/lifetime/gallon counter and self diagnostics.

Flat-Proof Tires Roll through even the worst jobsite debris without ever going flat.

FastFlush Cleaning System Cleans the unit up to 4X faster using only half the water!

WatchDog Save the pump from damage when paint runs out or if a hose breaks.

Additional 50 ft of Hose Gives you the versatility to work farther away from the sprayer.

TexSpray Mark IV

Texture spraying is all about high productivity, and that's where the Mark IV sprayer really delivers. Designed to save time and money by enabling you to spray more square footage in a day, this unit offers valuable, must-have features for the serious professional contractor. Whether you need to spray skim coat in a Level 5 finish, drywall mud in an orange peel, splatter or knockdown finish or even the wide range of primers and paint, this sprayer can do it all!

SERIES	AVAILABLE IN
STANDARD	120 VOLT
STANDARD	240 VOLT
PROCONTRACTOR	120 VOLT
PROCONTRACTOR	240 VOLT
120 VOLT SPECIFICATIONS	
MAX TIP SIZE:	.033
MAX LPM:	4.1
MAX PSI (BAR):	3300 (227)
MOTOR:	2.2 hp Brushless DC
240 VOLT SPECIFICATIONS	
MAX TIP SIZE:	.031
MAX LPM:	3.6
MAX PSI (BAR):	3300 (227)
MOTOR:	2.0 hp Brushless DC

- INCLUDES**
- Flex Plus Gun
 - LTX425 SwitchTip and Guard
 - 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless Hose
 - 1/4 in x 3 ft (6.4 mm x 0.9 m) Whip Hose

Standard Series

EVERYDAY RELIABILITY



Standard Series features found Only On A Graco:

Advantage Drive System Runs quiet and has a lifetime guarantee.

SmartControl 3.0 Pressure Control Delivers consistent spray fan without pressure fluctuations at all spraying pressures.

Endurance Pump with Max Flo+ Submerged foot valve easily handles the thickest materials.

Ceramic and Stainless Steel Ball Sets Provides maximum versatility no matter what you're spraying.

MaxPower Brushless DC Motor Never change brushes with this maintenance-free, totally enclosed, high torque motor.

Rugged Cart Design Chrome over steel makes this durable cart last for years.

Easy Out Pump Filter Less mess when changing or cleaning the filter.

Heavy-Duty Prime Valve Maintenance-free design withstands high pressure dumping.

Choose a Series
that's built
FOR YOU!

ProContractor Series

WORK SMARTER, FINISH MORE JOBS



All the features of the Standard Series, PLUS:

QuikReel Deploy and rewind up to 300 feet of hose in seconds without twists, kinks or coils.

Ready To Spray A total of 100 feet of hose and gun already installed.


ProConnect 2 Change out the pump using no tools in seconds resulting in quickly getting back to work.

LED Display Bright easy-to-read LED display shows pressure readout, job/lifetime/gallon counter and self diagnostics.

FastFlush Cleaning System Cleans the unit up to 4X faster using only half the water!

WatchDog Save the pump from damage when material runs out or a hose breaks.

On-Board Toolbox End frustration and save time by never again searching for tips, filters, and tools.



"We use Graco because they get the productivity we need. Everything in this industry is about productivity."

Joey Vukelich, General Foreman
Performance Contracting, Inc.

TexSpray Mark

V



The Graco TexSpray Mark V is built to deliver a higher flow rate that lets you get the job done faster. It features 20 percent more productivity than the Mark IV and comes with an upgraded Heavy-Duty Texture Gun. It can accommodate a larger tip size, and has the power to spray skim coat in a Level 5 finish, drywall mud in an orange peel, splatter or knockdown finish or even the wide range of primers and paint.

SERIES	AVAILABLE IN
STANDARD	120 VOLT
STANDARD	240 VOLT
PROCONTRACTOR	120 VOLT
PROCONTRACTOR	240 VOLT
IRONMAN	120 VOLT
IRONMAN	240 VOLT
120 VOLT SPECIFICATIONS	
MAX TIP SIZE:	.039
MAX LPM:	5.1
MAX PSI (BAR):	3300 (227)
MOTOR:	2.8 hp Brushless DC
240 VOLT SPECIFICATIONS	
MAX TIP SIZE:	.035
MAX LPM:	4.5
MAX PSI (BAR):	3300 (227)
MOTOR:	2.2 hp Brushless DC

INCLUDES

- Heavy-Duty Texture Gun
- LTX425 SwitchTip and Guard
- 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless Hose
- 1/4 in x 3 ft (6.4 mm x 0.9 m) Whip Hose

Standard Series

EVERYDAY RELIABILITY



Standard Series features found Only On A Graco:

Advantage Drive System Runs quiet and has a lifetime guarantee.

SmartControl 3.0 Pressure Control Delivers consistent spray fan without pressure fluctuations at all spraying pressures.

Endurance Pump with Max Flo+ Submerged foot valve easily handles the thickest materials.

Ceramic and Stainless Steel Ball Sets Provides maximum versatility no matter what you're spraying.

MaxPower Brushless DC Motor Never change brushes with this maintenance-free, totally enclosed, high torque motor.

Rugged Cart Design Chrome over steel makes this durable cart last for years.

Easy Out Pump Filter Less mess when changing or cleaning the filter.

Heavy-Duty Prime Valve Maintenance-free design withstands high pressure dumping.

Choose a Series
that's built
FOR YOU!

ProContractor Series

WORK SMARTER, FINISH MORE JOBS



All the features of the Standard Series, PLUS:

QuikReel Deploy and rewind up to 300 feet of hose in seconds without twists, kinks or coils.

Ready To Spray A total of 100 feet of hose and gun already installed.

ProConnect 2 Change out the pump using no tools in seconds resulting in quickly getting back to work.

LED Display Bright easy-to-read LED display shows pressure readout, job/lifetime/gallon counter and self diagnostics.

FastFlush Cleaning System Cleans the unit up to **4X faster** using only half the water!

WatchDog Save the pump from damage when material runs out or a hose breaks.

On-Board Toolbox End frustration and save time by never again searching for tips, filters, and tools.

IronMan Series

BEYOND JOBSITE TOUGH



All the features of the Standard Series, PLUS:

MaxLife Extreme Duty Pump Keeps you working *longer* between repacks.

ProConnect 2 Change out the pump using no tools in seconds resulting in quickly getting back to work.

Roll Cage Frame Innovative steel design withstands rugged environments and protects critical sprayer components.

LED Display Bright easy-to-read LED display shows pressure readout, job/lifetime/gallon counter and self diagnostics.

Flat-Proof Tires Roll through even the worst jobsite debris without ever going flat.

FastFlush Cleaning System Cleans the unit up to **4X faster** using only half the water!

WatchDog Save the pump from damage when material runs out or if a hose breaks.

Additional 50 ft of Hose Gives you the versatility to work farther away from the sprayer.

Mark V 120/240 VOLT

TexSpray Mark X 240 Volt

The most powerful electric airless/texture sprayer — period!

The TexSpray Mark X 240 Volt is our most productive electric airless/texture unit. With nearly double the output of the Mark V, it is the sprayer of choice for serious professional contractors who take advantage of the 240 volt power available at a construction site or with a generator. A true powerhouse, it can easily spray skim coat in a Level 5 finish and drywall mud in an orange peel, splatter or knockdown finish. It can even apply the whole range of primers and paints.

SERIES	AVAILABLE IN
STANDARD	110V and 230V
PROCONTRACTOR	110V and 230V
SPECIFICATIONS	
MAX TIP SIZE:	0.045
MAX LPM:	7.9
MAX PSI (BAR):	3300 (227)
MOTOR:	4.0 hp Brushless DC

- INCLUDES**
- Heavy-Duty Inline Texture Gun
 - LTX531, LTX541 SwitchTips and Guard
 - 1/2 in x 50 ft (13 mm x 15 m) BlueMax II Airless Hose
 - 3/8 in x 3 ft (9.5 mm x 0.9 m) Whip Hose

Standard Series

EVERYDAY RELIABILITY



Standard Series features found Only On A Graco:

Advantage Drive System Runs quiet and has a lifetime guarantee.

SmartControl 3.0 Pressure Control Delivers consistent spray fan without pressure fluctuations at all spraying pressures.

Endurance Pump with Max Flo+ Submerged foot valve easily handles the thickest materials.

Ceramic and Stainless Steel Ball Sets Provides maximum versatility no matter what you're spraying.

MaxPower Brushless DC Motor Never change brushes with this maintenance-free, totally enclosed, high torque motor.

Rugged Cart Design Chrome over steel makes this durable cart last for years.

Easy Out Pump Filter Less mess when changing or cleaning the filter.

Heavy-Duty Prime Valve Maintenance-free design withstands high pressure dumping.

Choose a Series
that's built
FOR YOU!

ProContractor Series

WORK SMARTER, FINISH MORE JOBS



All the features of the Standard Series, PLUS:

QuikReel Deploy and rewind up to 300 feet of hose in seconds without twists, kinks or coils.

Ready To Spray A total of 100 feet of hose and gun already installed.

ProConnect 2 Change out the pump using no tools in seconds resulting in quickly getting back to work.

LED Display Bright easy-to-read LED display shows pressure readout, job/lifetime/gallon counter and self diagnostics.

WatchDog Save the pump from damage when material runs out or a hose breaks.

On-Board Toolbox End frustration and save time by never again searching for tips, filters, and tools.



"The reason I use the Mark sprayer is because of the productivity and how much footage we get everyday."

Ron Fuller, General Foreman
Anning-Johnson

Mark X 240 VOLT

Accessories

ELECTRIC AIRLESS SPRAYERS

In addition to the industry's best sprayers, Graco makes the accessories that enable you to work faster and more productively. From rugged guns and tips to hoses and extensions, Graco's accessories let you customize your sprayer for the maximum performance that best suits your work.

FOR SPRAYERS: 390 – Ultra Max II 495 (All 110 Volt and 230 Volt Models)

DIGITAL DISPLAYS Simple to use and easy to install display featuring pressure display and error code self diagnostics.

- 287098 Digital Display for Ultra 395
- 287904 Digital Display for Ultra Max II 490/495



HOPPER 1.5-gallon molded hopper attaches to sprayer in place of inlet suction hose. Ideal for spraying small amounts of material. Lid included. Smooth inside cleans up fast. Works with Stand, Hi-Boy and Lo-Boy sprayers.

- 288526 Hopper Accessory



FILTERS AND INLET STRAINER

- 246425 Easy Out Filters – Short, Gray, 30 mesh
- 246384 Easy Out Filters – Short, Black, 60 mesh
- 246382 Easy Out Filters – Short, Blue, 100 mesh
- 246383 Easy Out Filters – Short, Red, 200 mesh



- 246385 Inlet Strainer



FOR SPRAYERS: Ultra Max II 695 – 1095 (All 110 Volt and 230 Volt Models)

LED DISPLAY Bright easy-to-read LED display shows pressure readout, job/lifetime, gallon counter and self diagnostics.

- 24V061 LED Display for SmartControl 3.0 fits Ultra Max II 695/795/1095
Fits all SmartControl 3.0 models. Includes WatchDog feature.



SUCTION HOSE KIT Easily installs on any sprayer to provide the convenience of a flexible inlet hose. Leave tube long (fits 30-gallon trash cans and 55-gallon drums) or simply unscrew at middle fitting to shorten (fits 5-gallon buckets).

- 248317 55 Gallon Suction Hose Kit

FILTERS AND STRAINERS

- 244071 Easy Out Filters – Long, Gray, 30 mesh
- 244067 Easy Out Filters – Long, Black, 60 mesh
- 244068 Easy Out Filters – Long, Blue, 100 mesh
- 244069 Easy Out Filters – Long, Red, 200 mesh
- 189920 Inlet Screen – Ultra Max II 695/795/1095
- 257033 Inlet Screen – IronMan 1095



FOR SPRAYERS: 390 – Ultra Max II 1095 (All 110 Volt and 230 Volt Models)

RAC X SWITCHTIP The RAC X SwitchTip is a high-performance spray tip used for residential and commercial applications. With a large selection of tip sizes available we are sure to have one to fit your needs. RAC X provides the best fan pattern life and the highest quality finish. These Graco tips are the most widely used reversible spray tip on the market today!



CONTRACTOR/FTx GUNS Designed by Graco to be the longest-lasting guns on the market, the Contractor and FTx Guns continue to be the number one choice of painting contractors. With features like the FlexSeal design, Easy Out Gun Filter and EasyGlide Swivel, no wonder these are the contractors choice in guns.

- 288420 Contractor Gun (2-finger trigger) with RAC X 517 Tip and Guard
- 288425 Contractor Gun (4-finger trigger) with RAC X 517 Tip and Guard
- 288421 Contractor Gun (2-finger trigger) with RAC® 5 517 Tip and Guard
- 288430 FTx Gun (4-finger trigger) with RAC X 515 Tip and Guard
- 288429 FTx Gun (2-finger trigger) with RAC X 515 Tip and Guard
- 288431 FTx Gun (4-finger trigger) with RAC 5 515 Tip and Guard
- 246240 Silver Plus Gun with RAC X 517 Tip and Guard
- 246468 Flex Plus™ Gun with RAC X 517 Tip and Guard
- 287023 3 ft (0.9 m) Pole Gun with Contractor Inline Valve, CleanShot™ Valve, RAC X Tip and Guard
- 287024 6 ft (1.8 m) Pole Gun with Contractor Inline Valve, CleanShot Valve, RAC X Tip and Guard



GUN HOSE KITS – KITS INCLUDE THE FOLLOWING UNLESS OTHERWISE NOTED

- Airless Gun, RAC X 517 Tip and Guard, 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II 3300 psi (227 bar) Airless Hose and 3 ft (0.9 m) Whip Hose
- 288489 Contractor Gun Hose Kit
- 288496 Contractor Gun Hose Kit with RAC 5
- 288490 Contractor Gun Hose Kit with 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II 3300 psi (227 bar) Airless Hose
- 288493 FTx Gun Hose Kit with RAC X 515 Tip (Whip Hose excluded)
- 288497 FTx Gun Hose Kit with RAC 5 515 Tip (Whip Hose excluded)
- 287095 Flex Plus Gun Hose Kit
- 287041 Silver Plus Gun Hose Kit
- 287042 Silver Plus Gun Hose Kit with 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II 3300 psi (227 bar) Airless Hose



BLUEMAX II AIRLESS HOSE To maximize results, choose the high performance BlueMax II Airless Hose. Lighter weight and increased hose flexibility improves usability when spraying under pressure. With superior flexibility and durability, BlueMax II ensures you get the best results from your airless sprayer.

- 238358 3/16 in x 3 ft (4.8 mm x 0.9 m) BlueMax II 3300 psi (227 bar) Airless Whip Hose
- 238959 3/16 in x 4.5 ft (4.8 mm x 1.4 m) BlueMax II 3300 psi (227 bar) Airless Whip Hose
- 240793 1/4 in x 25 ft (6.4 mm x 7.5 m) BlueMax II 3300 psi (227 bar) Airless Hose
- 240794 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II 3300 psi (227 bar) Airless Hose
- 240797 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II 3300 psi (227 bar) Airless Hose



Ask your local authorized Graco Distributor for details on our complete line of airless accessories.

FOR SPRAYERS: 390 – Ultra Max II 1095 (All 110 Volt and 230 Volt Models)

PUMP ARMOR™/TSL™ Maintaining your pump is essential for long life and reliability. Graco has made pump maintenance simple with our complete line of fluids. Pump Armor is a storage solution which protects your pump from the damaging effects of corrosion during storage. TSL (Throat Seal Liquid) prevents dried paint from accumulating on the pump rod—extending the life of the pump packings.

- 243103 Pump Armor – 1 liter
- 245133 Pump Armor – 3.8 liters
- 206994 Throat Seal Liquid (TSL) – .24 liter
- 206995 Throat Seal Liquid (TSL) – 1 liter
- 206996 Throat Seal Liquid (TSL) – 3.8 liters



JETROLLERS™ Save time and money by spraying and back rolling in one easy step with the **NEW** Graco 3-in-1 JetRoller System. Each kit includes a lightweight detachable roller (uses industry standard roller covers), CleanShot shut-off valve, spray tip and guard.

- 24U170 JetRoller System with 20 in (50 cm) Heavy-Duty Extension
- 24U171 JetRoller System with 18-36 in (49-91 cm) Telescoping Extension
- 24U172 JetRoller System with 20 in (50 cm) Heavy-Duty Extension and Contractor Inline Valve



PRESSURE ROLLERS

- 245397 EvenFlow™ Pressure Roller Assembly with 20 in (50 cm) Fixed, Heavy-Duty Extension and Contractor Inline Valve
- 244279 EvenFlow Pressure Roller Assembly with 20 in (50 cm) Fixed, Heavy-Duty Extension, 45° Angle
- 244281 EvenFlow Pressure Roller Assembly with 18-36 in (46-91 cm) Telescoping Extension



FOR TexSpray SPRAYERS: Mark IV & Mark V 120/240 Volt, Mark X 240 Volt

GUNS

- 246468 Flex Plus Gun
- 241705 Heavy-Duty Blue Texture Gun
- 245820 Inline Heavy-Duty Texture Gun



GUN HOSE KITS

- 241338 Heavy-Duty Blue Texture Gun Hose Kit with 531 RAC X SwitchTip 3/8 in x 50 ft (9.5 mm x 15 m) 3300 psi Hose, 1/4 in x 3 ft (25 mm x 0.9 m) 3300 psi Whip Hose, Couplers and additional 427 RAC X SwitchTip
- 289585 Inline Heavy-Duty Texture Gun Hose Kit with LTX643 SwitchTip 1/2 in x 50 ft (13 mm x 15 m) 4000 psi Hose, 3/8 in x 12 ft (9.5 mm x 3.6 m) Whip Hose, Swivel and Fittings



HOPPER

- 287987 25 Gallon (95 Liter) Texture Hopper Directly connects to Mark IV, Mark V, Mark X 240 Volt.

ADDITIONAL ACCESSORIES

- 244052 Heavy-Duty Texture Gun Air Atomizer Kit with Air Hose Minimum air compressor rating of 15 cfm at 90 psi.
- 244223 Heavy-Duty Texture Gun Air Atomizer Kit without Air Hose Minimum air compressor rating of 15 cfm at 90 psi
- 289669 208-Liters Siphon Kit for Mark X 240 Volt



WARRANTY SPRAY PROTECTION

We stand behind every piece of equipment we manufacture with the industry's strongest warranty. Spray with the confidence that you will probably never need to use Graco's warranty, but if you do... *we will be there.*

3-YEAR WARRANTY Coverage against defects in materials and workmanship on the entire sprayer.

NOBODY ELSE BUILDS SPRAYERS LIKE THIS.

ELECTRIC AIRLESS SPRAYER SPECIFICATIONS

		390 / 390S	Ultra 395	Ultra Max II 490	Ultra Max II 495
SPECIFICATIONS	Maximum Tip Size	0.021	0.021	0.025	0.025
	Maximum psi (bar)	3300 (227)	3300 (227)	3300 (227)	3300 (227)
	Maximum lpm	1.8	2.0	2.3	2.3
	Motor hp	5/8 DC	7/8 TEFC DC	1.0 Brushless DC	1.2 Brushless DC
	Weight kg	14 Stand	19 Stand	15 Stand	15 Stand
	Gun Support:				
	1 Gun	0.021	0.023	0.023	0.025
2 Guns	—	—	—	—	
3 Guns	—	—	—	—	



MODEL	Cart Design-Part Number	253958-Stand 110 Volt 24U104-390S Stand 230 Volt 262019-Hi-Boy 110 Volt 24U107-390S Hi-Boy 230 Volt	233960- Stand 110 Volt 234180- Stand 230 Volt 233962- Hi-Boy 110 Volt 234286- Hi-Boy 230 Volt	249911-Stand 110 Volt 249932-Stand 230 Volt 249914-Hi-Boy 110 Volt 253013 Hi-Boy 230 Volt	249915-Stand 110 Volt 249933-Stand 230 Volt 249916-Lo-Boy 110 Volt 253104-Lo-Boy 230 Volt 249917-Hi-Boy 110 Volt 253105-Hi-Boy 230 Volt
INCLUDES	Gun	FTx	Contractor	Contractor	Contractor
	Hose	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless
	Tip	RAC X 515	RAC X 517	RAC X 517	RAC X 517
	Filter	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out
ENDURANCE PUMP	Type	QuikChange System	QuikChange System	QuikChange System	QuikChange System
	Rod	Chromex	Chromex	Chromex	Chromex
	Cylinder	Hardened SST	Hardened SST	Hardened SST	Hardened SST
CONTROL & DRIVE	Control	Electronic	SmartControl 1.0	SmartControl 2.0	SmartControl 2.0
	Motor	DC	TEFC DC	MaxPower	MaxPower
ENDURANCE PUMP	Replacement Pump	246428	246428	246428	246428
WEAR PARTS	Repair Kit	244194	244194	244194	244194
	Rod	249125	249125	249125	249125
	Cylinder	243176	243176	243176	243176
	Intake Seat Kit	246429	246429	246429	246429
MANUAL	Operation	311732	309665	309665	309665
	Parts	311761	309675	309675	309675

		Ultra Max II 695	Ultra Max II 795
SPECIFICATIONS	Maximum Tip Size	0.031	0.033
	Maximum psi (bar)	3300 (227)	3300 (227)
	Maximum lpm	3.6	4.1
	MaxPower Motor hp	2.0 Brushless DC	2.2 Brushless DC
	Control	SmartControl 3.0	SmartControl 3.0
	Weight kg	42 Standard Hi-Boy	44 Standard
	Gun Support:		
1 Gun	0.031	0.033	
2 Guns	0.023	0.025	
3 Guns	—	0.019	



SERIES TYPE		STANDARD	PROCONTRACTOR	STANDARD	PROCONTRACTOR
MODEL	Cart Design-Part Number	16W892-Hi-Boy 110 Volt 16X660-Hi-Boy 230 Volt 16W893-Lo-Boy 110 Volt 16X812-Lo-Boy 230 Volt	16W894-110 Volt 16Y639-230 Volt	16W895-110 Volt 16X870-230 Volt	16W896-110 Volt 16Y895-230 Volt
	Gun	Contractor	Contractor	Contractor	Contractor
INCLUDES	Hose	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) AND 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) AND 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless
	Tip	RAC X 517	RAC X 517	RAC X 517	RAC X 517
	Filter	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out
	PUMP	Type	QuikChange System	ProConnect System	QuikChange System
ADDITIONAL SERIES FEATURES	Rod	Chromex	Chromex	Chromex	Chromex
	Sleeve	Hardened SST	Hardened SST	Hardened SST	Hardened SST
	—	—	QuikReel	—	QuikReel
	—	—	FastFlush	—	FastFlush
	—	—	LED Display	—	LED Display
	—	—	WatchDog	—	WatchDog
WEAR PARTS	—	—	On-Board Toolbox	—	On-Board Toolbox
	Replacement Pump	16Y598	16Y414	16Y598	16X414
	Repair Kit	248212	248212	248212	248212
	Rod	248206	16X434	248206	16X434
	Sleeve	248209	248209	248209	248209
MANUAL	Intake Seat Kit	239922	239922	239922	239922
	Operation	332916	332916	332916	332916
	Parts	332918	332918	332918	332918
Pump	333028	332922	333028	332922	

ELECTRIC AIRLESS SPRAYER SPECIFICATIONS CONTINUED

		Ultra Max II 1095
SPECIFICATIONS	Maximum Tip Size	0.035
	Maximum psi (bar)	3300 (227)
	Maximum lpm	4.9
	MaxPower Motor hp	2.4 Brushless DC
	Control	SmartControl 3.0
	Weight kg	55 Standard
	Gun Support:	
1 Gun	0.035	
2 Guns	0.027	
3 Guns	0.021	



SERIES TYPE		STANDARD	PROCONTRACTOR	IRONMAN
-------------	--	----------	---------------	---------

MODEL	SERIES TYPE			
	Part Number	STANDARD	PROCONTRACTOR	IRONMAN
Gun	Contractor	Contractor	Contractor	Silver Plus
Hose	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) AND 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) AND 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) AND RAC X 517, RAC X Wide RAC 1231
Tip	RAC X 517	RAC X 517	RAC X 517	RAC X 517, RAC X Wide RAC 1231
Filter	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out
PUMP	Type	QuikChange System	ProConnect System	ProConnect System
	Rod	Chromex	Chromex	MaxLife
	Sleeve	Hardened SST	Hardened SST	MaxLife
ADDITIONAL SERIES FEATURES		-	QuikReel	Roll Cage Frame
		-	FastFlush	FastFlush
		-	LED Display	LED Display
		-	WatchDog	WatchDog
		-	On-Board Toolbox	Flat-Proof Tires
WEAR PARTS	Replacement Pump	16Y706	16X419	16X420
	Repair Kit	248213	248213	248213/16X430*
	Rod	248207	16X435	16X436
	Sleeve	248210	248210	257031
	Intake Seat Kit	244199	244199	244199
MANUAL	Operation	332916	332916	332916
	Parts	332918	332918	332918
	Pump	333028	332922	332922

TexSpray Mark IV	
120 Volt	240 Volt

SPECIFICATIONS	Maximum Tip Size	0.033	0.031
	Maximum psi (bar)	3300 (227)	3300 (227)
	Maximum lpm	4.1	3.6
	MaxPower Motor hp	2.2 hp Brushless DC	2.0 hp Brushless DC
	Control	SmartControl 3.0	SmartControl 3.0
	Weight kg	49	49
	Compressor Air Output	Compressor and Air Atomizer Kit required for some texture finishes.	Compressor and Air Atomizer Kit required for some texture finishes.



SERIES TYPE		STANDARD	PROCONTRACTOR
-------------	--	----------	---------------

MODEL	SERIES TYPE		
	Part Number	STANDARD	PROCONTRACTOR
Gun	Contractor	Contractor	Silver Plus
Hose	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) AND 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) AND 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless
Tip(s)	RAC X 425	RAC X 425	RAC X 425
Filter	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out
PUMP	Type	QuikChange System	ProConnect 2
	Rod	Chromex	Chromex
	Sleeve	Hardened SST	Hardened SST
ADDITIONAL SERIES FEATURES		-	QuikReel
		-	FastFlush
		-	LED Display
		-	WatchDog
		-	On-Board Toolbox
		-	On-Board Toolbox
MANUAL	Operation	332916	332916
	Parts	332918	332918
TYPICAL APPLICATIONS	Materials Sprayed	Oil-based coatings, enamels, latex, block-fillers, elastomerics, epoxies, drywall mud and other high-build materials	Oil-based coatings, enamels, latex, block-fillers, elastomerics, epoxies, drywall mud and other high-build materials
	Surfaces	Medium to large residential and commercial interiors and exteriors	Medium to large residential and commercial interiors and exteriors

TexSpray Mark V	
120 Volt	240 Volt

SPECIFICATIONS	Maximum Tip Size	0.039	0.035
	Maximum psi (bar)	3300 (227)	3300 (227)
	Maximum lpm	5.1	4.5
	MaxPower Motor hp	2.8 hp Brushless DC	2.2 hp Brushless DC
	Control	SmartControl 3.0	SmartControl 3.0
	Weight kg	61	61
	Compressor Air Output	Compressor and Air Atomizer Kit required for some texture finishes.	Compressor and Air Atomizer Kit required for some texture finishes.



SERIES TYPE		STANDARD	PROCONTRACTOR	IRONMAN
-------------	--	----------	---------------	---------

MODEL	SERIES TYPE			
	Part Number	STANDARD	PROCONTRACTOR	IRONMAN
Gun	Contractor	Contractor	Contractor	Silver Plus
Hose	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) AND 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) AND 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) AND RAC X 517, RAC X Wide RAC 1231
Tip(s)	RAC X 425	RAC X 425	RAC X 425	RAC X 425
Filter	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out
PUMP	Type	QuikChange System	ProConnect 2	ProConnect 2
	Rod	Chromex	Chromex	Chromex
	Sleeve	Hardened SST	Hardened SST	Hardened SST
ADDITIONAL SERIES FEATURES		-	QuikReel	Roll Cage Frame
		-	FastFlush	LED Display
		-	LED Display	WatchDog
		-	WatchDog	Flat-Proof Tires
		-	On-Board Toolbox	FastFlush
		-	On-Board Toolbox	FastFlush
MANUAL	Operation	332916	332916	332916
	Parts	332918	332918	332918
TYPICAL APPLICATIONS	Materials Sprayed	Oil-based coatings, enamels, latex, block-fillers, elastomerics, epoxies, drywall mud and other high-build materials	Oil-based coatings, enamels, latex, block-fillers, elastomerics, epoxies, drywall mud and other high-build materials	Oil-based coatings, enamels, latex, block-fillers, elastomerics, epoxies, drywall mud and other high-build materials
	Surfaces	Medium to large residential and commercial interiors and exteriors	Medium to large residential and commercial interiors and exteriors	Large commercial and industrial interiors and exteriors

TexSpray Mark X	
240 Volt	

SPECIFICATIONS	Maximum Tip Size	0.045
	Maximum psi (bar)	3300 (227)
	Maximum lpm	7.9
	MaxPower Motor hp	4.0 hp Brushless DC
	Control	SmartControl 3.0
	Weight kg	64
	Compressor Air Output	Compressor and Air Atomizer Kit required for some texture finishes.



SERIES TYPE		STANDARD	PROCONTRACTOR
-------------	--	----------	---------------

MODEL	SERIES TYPE		
	Part Number	STANDARD	PROCONTRACTOR
Gun	Contractor	Contractor	Silver Plus
Hose	1/2 in x 50 ft (13 mm x 15 m)	1/2 in x 50 ft (13 mm x 15 m)	1/2 in x 100 ft (13 mm x 30 m)
Tip(s)	RAC X 531 and 541	RAC X 531 and 541	RAC X 531 and 541
Filter	60 Mesh Easy Out	60 Mesh Easy Out	60 Mesh Easy Out
PUMP	Type	QuikChange System	ProConnect 2
	Rod	Chromex	Chromex
	Sleeve	Hardened SST	Hardened SST
ADDITIONAL SERIES FEATURES		-	QuikReel
		-	FastFlush
		-	LED Display
		-	WatchDog
		-	On-Board Toolbox
		-	On-Board Toolbox
MANUAL	Operation	332916	332916
	Parts	332918	332918
TYPICAL APPLICATIONS	Materials Sprayed	Oil-based coatings, enamels, latex, block-fillers, elastomerics, epoxies, drywall mud and other high-build materials	Oil-based coatings, enamels, latex, block-fillers, elastomerics, epoxies, drywall mud and other high-build materials
	Surfaces	Large residential and commercial interiors and exteriors	Large residential and commercial interiors and exteriors



ABOUT GRACO

PROVEN QUALITY. LEADING TECHNOLOGY.

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

GRACO LOCATIONS

MAILING ADDRESS

P.O. Box 1441
Minneapolis, MN 55440-1441
Tel: 612-623-6000
Fax: 612-623-6777

AMERICAS

MINNESOTA

Worldwide Headquarters
Graco Inc.
88-11th Avenue N.E.
Minneapolis, MN 55413

EUROPE

BELGIUM

European Headquarters
Graco N.V.
Industrieterrein-Oude Bunders
Slakweidestraat 31
3630 Maasmechelen,
Belgium
Tel: 32 89 770 700
Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA

Graco Australia Pty Ltd.
Suite 17, 2 Enterprise Drive
Bundoora, Victoria 3083
Australia
Tel: 61 3 9468 8500
Fax: 61 3 9468 8599

CHINA

Graco Hong Kong Ltd.
Shanghai Representative Office
Building 7
1029 Zhongshan Road South
Huangpu District
Shanghai 200011
The People's Republic of China
Tel: 86 21 649 50088
Fax: 86 21 649 50077

INDIA

Graco Hong Kong Ltd.
India Liaison Office
Room 443, Augusta Point
Regus Business Centre 53
Golf Course Road
Gurgaon, Haryana
India 122001
Tel: 91 124 435 4208
Fax: 91 124 435 4001

JAPAN

Graco K.K.
1-27-12 Hayabuchi
Tsuzuki-ku
Yokohama City, Japan 2240025
Tel: 81 45 593 7300
Fax: 81 45 593 7301

KOREA

Graco Korea Inc.
Shinhan Bank Building
4th Floor #1599
Gwanyang-Dong, Dongan-Ku,
Anyang-si, Korea 431-060
Tel: 82 31 476 9400
Fax: 82 31 476 9801

SALES/ DISTRIBUTION/ SERVICE

Call today for product information or to request a demonstration.

800-690-2894 or visit us at www.graco.com.

Graco Inc. is registered to I.S. EN ISO 9001

North America
Customer Service
800-690-2894
Fax 800-334-6955